Refine Search

Search Results -

Term	Documents
(17 AND 16).PGPB,USPT,EPAB,JPAB,DWPI,TDBD.	4
(L16 AND L17).PGPB,USPT,EPAB,JPAB,DWPI,TDBD.	4

Database: US Pre-Grant Publication Full-Text Database; US Patents Full-Text Database; US OCR Full-Text Database; EPO Abstracts Database; JPO Abstracts Database; Derwent World Patents Index; IBM Technical Disclosure Bulletins

Search: L18

Refine Search | Recall Text | Clear | Interrupt

Search History

DATE: Monday, June 06, 2005 Printable Copy Create Case

Set Name side by side	Query	Hit Count	Set Name result set
DB=PGPB,USPT,EPAB,JPAB,DWPI,TDBD; THES=ASSIGNEE; PLUR=YES; OP=ADJ			
L18	l16 and L17	4	L18
L17	copy$ same instructions same proxy	52	L17
L16	network and L15	965	L16
L15	(proxy near2 server) and L14	978	L15
L14	(element or control module)same code	84249	L14
L13	l10 and L12	0	L13
L12	new near2 module	8203	L12
L11	l1 and L10	3	L11
L10	proxy server near2 code	65	L10
L9	proxy server near2 new code	0	L9
L8	copy$ and L7	1	L8
L7	network and L5	7	L7
L6	netwrok and L5	0	L6

L5	proxy same new code	9	L5
L4	l1 and L3	1	L4
L3	new code and L2	118	L3
L2	proxy same code	2454	L2
L1	network near2 group	11811	L1

END OF SEARCH HISTORY

Mon, 6 Jun 2005, 3:42:57 PM EST

Edit an existing query or compose a new query in the Search Query Display.

Select a search number (#) to:

- Add a query to the Search Query Display
- Combine search queries using AND, OR, or NOT
- Delete a search
- Run a search

Search Query Display

Recent Search Queries

#1 ((proxy server and new code)<in>metadata)

#2 ((proxy server and new code)<in>metadata)

#3 ((proxy server and new code)<in>metadata)

#4 (proxy server<in>metadata) <and> (new code<in>metadata)

#5 (network<in>metadata) <and> (proxy server<in>metadata) <and> (code<in>metadata)

#6 (network<in>metadata) <and> (proxy server<in>metadata) <and> (code<in>metadata)

#7 (network<in>metadata) <and> (proxy server<in>metadata) <and> (code<in>metadata)

#8 (network<in>metadata) <and> (proxy server<in>metadata) <and> (code<in>metadata)

#9 (network<in>metadata) <and> (proxy server<in>metadata) <and> (code<in>metadata)

#10 (network<in>metadata) <and> (proxy server<in>metadata) <and> (code<in>metadata)

Functionality adaptation: a context-aware service code ac pervasive computing environments

Vivien Wai-Man Kwan Francis Chi-Moon Lau Cho-Li Wang
Dept. of Comput. Sci. & Inf. Syst., Hong Kong Univ., China

This paper appears in: **Web Intelligence, 2003. WI 2003. Proceedings. IEEE/WIC Inter on**
Publication Date: 13-17 Oct. 2003
On page(s): 358 - 364
Number of Pages: xxi+730
ISSN:
INSPEC Accession Number:7922634
Posted online: 2003-10-27 09:54:52.0

Abstract
Pervasive computing has attracted a lot of attention in recent years. There are now **proxy** specially designed for pervasive computing. To enable content viewing in small devices, content adaptation techniques have been used (such as distillation and transcoding) to a content-rich servers to resource-constrained devices. Adaptation of Web contents has be but little attention was paid to the adaptation of services (or service **code**), which is equal computing anytime, anywhere, and on any device. We present an approach to adaptatio which is proxy-based and context-aware, called "functionality adaptation". The main diffic adaptation is to estimate the resource usage required for an execution, which varies with available only at run-time. We propose a conservative solution. A simple prototype has b evaluate our adaptation approach.

Index Terms
Inspec
Controlled Indexing
Internet **network** servers resource allocation ubiquitous computing

Non-controlled Indexing
Web contents content adaptation techniques context-aware service **code** adap pervasive computing environment **proxy servers**
Author Keywords
Not Available

References

No references available on IEEE Xplore.

Citing Documents

No citing documents available on IEEE Xplore.